



Modèle	Unité intérieure	MSZ-HR25VF	MSZ-HR35VF	MSZ-HR42VF	MSZ-HR50VF	MSZ-HR60VF	MSZ-HR71VF
	Unité extérieure	MUZ-HR25VF	MUZ-HR35VF	MUZ-HR42VF	MUZ-HR50VF	MUZ-HR60VF	MUZ-HR71VF

Unité intérieure

Débit d'air (PV / GV) (m³/h)	216 / 582	216 / 702	360 / 786	384 / 786	624 / 1176	624 / 1176
Pression sonore à 1 m (dB(A))	21 / 43	22 / 46	24 / 45	28 / 45	33 / 50	33 / 50
Dimensions (LxPxH) (mm)	838 x 228 x 280	838 x 228 x 280	838 x 228 x 280	838 x 228 x 280	923 x 262 x 305	923 x 262 x 305
Poids (kg)	8.5	8.5	9.0	9.0	12.5	12.5

Unité extérieure

Débit d'air (m³/h)	1818	192	2058	2058	2568	2568
Pression sonore à 1 m (dB(A))	50	51	51	51	53	53
Dimensions (LxPxH) (mm)	699 x 249 x 538	699 x 249 x 538	800 x 285 x 550	800 x 285 x 550	800 x 285 x 714	800 x 285 x 714
Poids (kg)	23	24	34	35	40	40

Réfrigérant

Fluide	R-32	R-32	R-32	R-32	R-32	R-32
Charge (kg)	0.4	0.45	0.7	0.8	1.05	1.05
Longueur préchargée (m)	7	7	7	7	7	7
Charge additionnelle (g/m)	20	20	20	20	20	20

Tuyauterie

Liquide (pouce)	1/4	1/4	1/4	1/4	1/4	1/4
Gaz (pouce)	3/8	3/8	3/8	3/8	1/2	1/2
Longueur mini / maxi (m)	3 / 20	3 / 20	3 / 20	3 / 20	3 / 30	3 / 30
Dénivelé maxi (m)	15	15	15	15	15	15

Alimentation électrique

Tension	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50
Protection (A)	10	10	10	10	16	16
Câble alimentation (mm²)	3G 2.5	3G 2.5	3G 2.5	3G 2.5	3G 2.5	3G 2.5
Interconnexion (mm²)	4G 1.5	4G 1.5	4G 1.5	4G 1.5	4G 2.5	4G 2.5



MUZ-HR 25 / 35



MUZ-HR 42 / 50



MUZ-HR 60 / 71