



EVAPORADORES HISPANIA

SERIE HEA - CÚBICOS COMERCIALES



| Código | Modelo | (kW) | | Superf. (m ²) | Vol. (dm ³) | Conexiones (mm) | | | Ventilador | | | | | Potencia desescarche (W) | Peso (kg) |
|---------|----------------|------------------|-------------------|---------------------------|-------------------------|-----------------|--------|----|------------|-----|------|-------------------|------|--------------------------|-----------|
| | | T° -8°C ΔT 8K | T° -25°C ΔT 7K | | | Entrada | Salida | N° | V | W | I(A) | m ³ /h | Tiro | | |
| MF01921 | HEA 2501 09 4D | 1,25 | 0,90 | 8,92 | 1,8 | 12 | 16 | 1 | 230V-I | 44 | 0,20 | 800 | 4 | 1320 | 14 |
| MF01922 | HEA 2502 17 4D | 2,61 | 2,07 | 17,24 | 3,2 | | 19 | 2 | | 88 | 0,40 | 1600 | 5 | 2190 | 25 |
| MF01925 | HEA 2506 52 4D | 7,86 | 6,29 | 50,54 | 8,7 | 15 | 28 | 6 | | 264 | 1,20 | 4800 | 10 | 5670 | 70 |
| MF01926 | HEA 3001 12 4D | 1,91 | 1,55 | 11,89 | 2,4 | 12 | 19 | 1 | | 62 | 0,28 | 1350 | 6 | 1760 | 19 |
| MF01927 | HEA 3002 23 4D | 4,02 | 3,27 | 22,99 | 4,3 | | 22 | 2 | | 124 | 0,56 | 2700 | 7 | 2920 | 32 |
| MF01931 | HEA 4001 20 4D | 4,24 | 3,44 | 20,81 | 3,5 | 12 | 19 | 1 | | 160 | 0,73 | 3250 | 11 | 2750 | 30 |
| MF01932 | HEA 4002 40 4D | 8,74 | 6,85 | 39,77 | 7,2 | | 22 | 2 | | 320 | 1,46 | 6500 | 13 | 5150 | 57 |



| Código | Modelo | (kW) | | Superf. (m ²) | Vol. (dm ³) | Conexiones (mm) | | | Ventilador | | | | | Potencia desescarche (W) | Peso (kg) |
|---------|----------------|------------------|-------------------|---------------------------|-------------------------|-----------------|--------|----|------------|-----|------|-------------------|------|--------------------------|-----------|
| | | T° -8°C ΔT 8K | T° -25°C ΔT 7K | | | Entrada | Salida | N° | V | W | I(A) | m ³ /h | Tiro | | |
| MF01945 | HEA 2502 11 6D | 2,29 | 1,81 | 11,84 | 3,2 | 12 | 19 | 2 | 230V-I | 88 | 0,40 | 1660 | 5 | 2190 | 23 |
| MF01946 | HEA 2503 17 6D | 3,44 | 2,77 | 17,56 | 4,7 | | 22 | 3 | | 132 | 0,60 | 2490 | 6 | 3090 | 33 |
| MF01950 | HEA 3002 15 6D | 3,43 | 2,82 | 15,79 | 4,3 | | | 3 | | 2 | 124 | 0,56 | 2780 | 7 | 2920 |
| MF01951 | HEA 3003 23 6D | 5,26 | 4,27 | 23,41 | 6,2 | | 3 | | | 186 | 0,84 | 4170 | 9 | 4120 | 43 |
| MF01956 | HEA 4003 36 6D | 10,70 | 8,24 | 36,21 | 9,6 | 15 | 28 | 3 | | 480 | 2,19 | 10050 | 16 | 6550 | 68 |

(*). Rendimientos calculados en R-449A