



SINGLE-SPLIT WALL MOUNTED TYPE

Premium Series

SRK-ZS-W



Colour variation available

Users can choose their favorite colour from three choices.



Black & White (-WB)



Titanium (-WT)

SRK20ZS-W, SRK25ZS-W,
SRK35ZS-W, SRK50ZS-W

Pure White(-W)




Wireless Control System (option)



Wireless remote control



SRC20ZS-W, SRC25ZS-W2
SRC35ZS-W2



SRC50ZS-W

KEY FEATURES

- Elegant, timeless design, best suited for small to medium sized living spaces.
- Users can choose a color they like from three different choices.
- Low Global Warming Potential (GWP) and High energy efficiency by new refrigerant R32.
- Quiet Air Flow & Long Reach is achieved by jet technology.
- Allergen clear operation cleans air, using a control scheme owned only by Mitsubishi Heavy Industries Thermal Systems.
- Wireless interface control (optional).

SPECIFICATIONS

Indoor unit			SRK20ZS-W,-WB,-WT	SRK25ZS-W,-WB,-WT	SRK35ZS-W,-WB,-WT	SRK50ZS-W,-WB,-WT
Outdoor unit			SRC20ZS-W	SRC25ZS-W2	SRC35ZS-W2	SRC50ZS-W
Power source			1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min~Max)		kW	2.0(0.9~2.9)	2.5(0.9~3.1)	3.5(0.9~4.0)	5.0(1.3~5.5)
Nominal heating capacity (Min~Max)		kW	2.7(0.9~4.3)	3.2(0.9~4.5)	4.0(0.9~5.0)	5.8(1.3~6.6)
Power consumption		Cooling/Heating	kW			
			0.44 / 0.59	0.62 / 0.74	0.89 / 0.94	1.35 / 1.56
EER/COP		Cooling/Heating				
			4.55 / 4.58	4.03 / 4.32	3.93 / 4.26	3.70 / 3.72
Max. running current		A	9			
Sound power level	Indoor	Cooling/Heating	9			
	Outdoor	Cooling/Heating	48 / 50	50 / 53	54 / 56	59 / 60
Sound pressure level	Indoor	Cooling/Heating	56 / 56			
	Outdoor	Cooling/Heating	56 / 58			
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	dB(A)			
	Outdoor	Cooling/Heating	34 / 25 / 22 / 19	36 / 28 / 23 / 19	40 / 30 / 26 / 19	46 / 36 / 29 / 22
Exterior dimensions	Indoor	HeightxWidthxDpth	mm			
	Outdoor		290 x 870 x 230			
Net weight	Indoor / Outdoor	kg	540 x 780(+62) x 290		595 x 780(+62) x 290	
			9.5 / 31.0		10.0 / 36.0	
Refrigerant	Type/GWP		R32 / 675			
	Charge	kg/TCO ₂ Eq	0.62 / 0.419		0.78 / 0.527	
Refrigerant piping size	Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")	
	Refrigerant line (one way) length [chargeless length]	m	Max. 20 [15]		Max. 25 [15]	
Vertical height differences	Outdoor is higher/lower	m	Max. 10 / Max. 10		Max. 15 / Max. 15	
	Outdoor operating temperature range	°CDB	-15~46			
Clean filter	Cooling		-15~24			
	Heating		Allergen Clear Filter x 1, Photocatalytic Washable Deodorising Filter x 1			

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.